



ELETTROQUADRI

Order N°	date / /
Reference	
Order Confirmation N°	
Delivery request	/ /

Customer
----------

**Elevator Type**

Hydro  Traction  MRL

**Mach. Room position**

Above  Below  At floor

**Machine room Bottom**

**Machine Room Above**

Open A	Floor designation																				Floor designation	Open A
	Contr. Distance																				Contr. Distance	
Open B	Floor designation																				Floor designation	Open B
	Contr. Distance																				Contr. Distance	

Distance Contr.-1<sup>st</sup> landing box  Main landing  Flat Traveling cable length

Distance Contr.-gear mach./pump  Distance Contr.-Power Contactors  Car door- central opening

Distance between guide rails > 1500 mm  Distance Front A-Rear B doors > 1500 mm  Speed limit device position

**BASE SUPPLY**

**CAR**

Flat Traveling cables pre-wired  
 Junction box  
 Top of Car Inspection box  
 'Reed' switches with magnet strips  
 Overtravel switch (traction elevator only)  
 CRD/CRS contacts as selected

Operator or door contact connection  
 Lighting connection  
 Car safety gear contact connection  
 Photocell connection  
 C.O.P. connection  
 Mt. 4 trunk 80x60

**HOISTWAY**

Hoistway harness  
 Landing box connections  
 Door lock connections  
 Stop in pit  
 Ext Extra-rise (hydro elevator only)  
 Alarm bell (1 every 5 stops)

Governor tensioner connection (traction elevator only)  
 N° 1 wedge flat traveling cable fasten  
 N° 2 brackets for fastening flat trav. cable  
 Trunk 60x40 + clamps (L=H hoistway)  
 Earth cable to guide rails

**MACHINE ROOM**

Power cable main switches-controller  
 Power cable controller-pump unit or gear machine  
 Mt. 2 trunk 150x80  
 N° 1 insulating tape

Conn. 4<sup>th</sup> pole (hydro elevator only)  
 Power cable for lighting  
 Cable for valves (hydro elevator only)  
 Kit of safety/warning plate

**Option L.13 (DM236)**

Intercom system Machine Room - Car  
 Gong for car roof  
 Alarm jewel connection for landing boxes panels

**Option 95/16**

Thermostat for Machine Room  
 Overload connection

**Option EN81.28**

Bi-Directional intercom device, type Esseti model Helpy L300  
 Porter for COP, car roof and pit

**Option EN81.70**

Pre-setting for audible calls  
 Voice synthesizer type Liftit, model VOX17P Lift.it(  
 Pre-setting photoelectric barrier

**Option EN81.72**

Junction box - protection grade IP X3  
 Alarm bell - protection grade IP X3  
 Landing hoisway plastic boxes - protection grade IP55

**Lighting In Hoistway**

N° 1 lamp to light the car roof per illuminazione tetto cabina  
 N°1 lamp in hoistway every 3 mt.  
 Branch switch between controller and shaft pit

**OTHER OPTIONS**

Display at Main or All landing as selected on controller

Car Direction at Main or All landing as selected on controller

Next Direction at landings as selected on controller

Main Power Switches devices:  with differential switch   
 w/o differential switch

Hall Lanterns above the doors

One LOP row only (for Duplex only)

Photoelectric barrier (EN 81.70)

GSM module

Photocell  Bertolotti   
 Telco

Slides :  over travel mechanical   
 for CRD/CRS mechanical

N° 2 slides with fastening for slowdown mach. switches

Bottoniere in conto lavoro

Double COP

COP supply (see COP ordering form)

Landing boxes supply (see HBB ordering form)

NOTE