



ELETTROQUADRI

Order N°	date / /
Reference	
Order Confirmation N°	
Delivery request	/ /

Customer

Elevator Type

Hydro Traction MRL

Mach. Room position

Above Below At floor

Machine room Bottom

Machine Room Above

Open A	Floor designation																			Floor designation	Open A
	Contr. Distance																			Contr. Distance	
Open B	Floor designation																			Floor designation	Open B
	Contr. Distance																			Contr. Distance	

Distance Contr.-1st landing box Main landing Flat Traveling cable length

Distance Contr.-gear mach./pump Distance Contr.-Power Contactors Car door- central opening

Distance between guide rails > 1500 mm Distance Front A-Rear B doors > 1500 mm Speed limit device position

BASE SUPPLY

CAR

Flat Traveling cables pre-wired
 Junction box
 Top of Car Inspection box
 'Reed' switches with magnet strips
 Overtravel switch (traction elevator only)
 CRD/CRS contacts as selected

Operator or door contact connection
 Lighting connection
 Car safety gear contact connection
 Photocell connection
 C.O.P. connection
 Mt. 4 trunk 80x60

HOISTWAY

Hoistway harness
 Landing box connections
 Door lock connections
 Stop in pit
 Ext Extra-rise (hydro elevator only)
 Alarm bell (1 every 5 stops)

Governor tensioner connection (traction elevator only)
 N° 1 wedge flat traveling cable fasten
 N° 2 brackets for fastening flat trav. cable
 Trunk 60x40 + clamps (L=H hoistway)
 Earth cable to guide rails

MACHINE ROOM

Power cable main switches-controller
 Power cable controller-pump unit or gear machine
 Mt. 2 trunk 150x80
 N° 1 insulating tape

Conn. 4th pole (hydro elevator only)
 Power cable for lighting
 Cable for valves (hydro elevator only)
 Kit of safety/warning plate

Option L.13 (DM236)

Intercom system Machine Room - Car
 Gong for car roof
 Alarm jewel connection for landing boxes panels

Option 95/16

Thermostat for Machine Room
 Overload connection

Option EN81.28

Bi-Directional intercom device, type Esseti model Helpy L300
 Porter for COP, car roof and pit

Option EN81.70

Pre-setting for audible calls
 Voice synthesizer type Liftit, model VOX17P Lift.it(
 Pre-setting photoelectric barrier

Option EN81.72

Junction box - protection grade IP X3
 Alarm bell - protection grade IP X3
 Landing hoisway plastic boxes - protection grade IP55

Lighting In Hoistway

N° 1 lamp to light the car roof per illuminazione tetto cabina
 N°1 lamp in hoistway every 3 mt.
 Branch switch between controller and shaft pit

OTHER OPTIONS

Display at Main or All landing as selected on controller

Car Direction at Main or All landing as selected on controller

Next Direction at landings as selected on controller

Main Power Switches devices: with differential switch
 w/o differential switch

Hall Lanterns above the doors

One LOP row only (for Duplex only)

Photoelectric barrier (EN 81.70)

GSM module

Photocell Bertolotti
 Telco

Slides : over travel mechanical
 for CRD/CRS mechanical

N° 2 slides with fastening for slowdown mach. switches

Bottoniere in conto lavoro

Double COP

COP supply (see COP ordering form)

Landing boxes supply (see HBB ordering form)

NOTE